



ABASCO Type 2 DOT Turbidity Curtain

ABASCO Type 2 DOT Turbidity Curtains include heavy duty tension members at the top and bottom of the curtain and premium 22 oz. PVC coated fabric. They are ideal for silt and sediment control during dredging and marine construction activities in areas exposed to mild current, wind and wave activity. Meets or exceeds most state DOT requirements.

Fabric	22 oz/yd ² PVC Coated Polyester Fabric. Optional filter fabric in skirt.
Flotation	8"-12" dia. (depending on skirt depth) EPS foam contained within Individually sealed float pockets
Top Tension	5/16" galvanized steel cable (9,800 lbs breaking strength) contained in a polyethylene tube
Bottom Tension & Ballast	5/16" galvanized steel chain (7,600 lbs breaking strength, 0.93 lbs/ft)
End Connectors	High tensile strength aluminum 'Universal' connector at float and top tension cable. ASTM 3/8" stainless steel locking pins. Grommets on reinforced fabric on lower skirt. Chain ends shackled section-to-section. Tool free connections. Aluminum stress plates at bottom corners.
Section Length	50/100 ft.
Skirt Depth	To 50 ft. Depth can be tapered to conform to bottom profile.
Furling Lines	Available on request
Accessories	Anchor Systems, Ropes, Marker Buoys, Solar Lights, Repair Kits

