



## ABASCO Type 3 Heavy Duty Turbidity Curtain

ABASCO Type 3 Turbidity Curtains include heavy duty tension members at the top and bottom of the curtain and high-strength fabrics. They are ideal for silt and sediment control during dredging and marine construction activities. For use in rivers, bays and waterways with moderate current, wind and wave activity.

Fabric	22 oz/yd <sup>2</sup> PVC Coated Polyester Fabric. Optional filter fabric in skirt.
Flotation	8"-24" dia. (depending on skirt depth) EPS foam contained within individually sealed float pockets
Top Tension	Two (2) ea. 5/16" galvanized steel cable (9,800 lbs breaking strength) contained in PE tube, one above float, one beneath float.
Bottom Tension & Ballast	3/8" galvanized steel chain (10,600 lbs breaking strength, 1.41 lbs/ft)
End Connectors	High tensile strength aluminum 'Universal' connector at float and top tension cable. ASTM 3/8" stainless steel locking pins. Grommets on reinforced fabric on lower skirt. Chain ends shackled section-to-section. Tool-free connections. All comers reinforced with 40 oz PVC fabric. Aluminum stress plates at bottom comers.
Length	50 & 100 ft. Standard
Skirt Depth	To 150 ft. Depth can be tapered to conform to bottom profile.
Furling Lines	Available on request
Accessories	Anchor Systems, Ropes, Marker Buoys, Solar Lights, Repair Kits

